



**POWER GENERATION DATA SHEET**

**UNREGULATED  
LINE-UP**

**20 – 580 kWm**

**Our efficiency.  
Your edge.**

# UNREGULATED

**20-580 kWm**



## Proven reliability and durability

FPT Industrial manufactures a range of dependable, emergency stationary power solutions that offer **low fuel consumption and maintenance costs** and the benefits of a compact footprint.

Our engine portfolio is available with mechanical or electronic injection system, natural aspirated or turbocharged.

**Flexibility to switch between 50 Hz to 60 Hz** allows an efficient stock management for the Customers.

## KEY FEATURES:

- Top performance in terms of power, load response and fuel consumption in all conditions.
- Quick to market solution thanks to G-Drive: pre-assembled cooling pack and air cleaner.
- Switchability from 1,500 rpm to 1,800 rpm.
- Best in class service interval: 600 hours.

## Unregulated

G-DRIVE

Engine Name	Engine Model	Displacement Litres	Cylinder Arrangement	Air intake	Exhaust System	Injection System	50 Hz / 1,500 rpm						60 Hz / 1,800 rpm						Typical Generator eff.	1,500/1,800 rpm Switchable		
							Stand-by Power			Prime Power			Stand-by Power			Prime Power						
							kWm (net)	kWe	kVA	kWm (net)	kWe	kVA	kWm (net)	kWe	kVA	kWm (net)	kWe	kVA				
R24	R24MANS01.23A02	2.4	4 L/NA/TC	M		M	23	20	24	23	20	24	24	20	25	24	20	25	88%	●		
R24	R24MSNS01.31A02	2.4	4 L/NA/TC	M		M	31	26	33	28	24	30	35	29	36	32	26	33	88%	●		
R24	R24MSNS01.40A02	2.4	4 L/NA/TC	M		M	40	34	42	36	30	38	40	33	41	36	30	37	88%	●		
N45	NEF45AM2	4.5	4L/NA	M		M	51	45	56	45	41	51	-	-	-	-	-	-	88%	○		
N45 <sup>1</sup>	NEF45SM1A	4.5	4L/TC	M		M	59	54	67	53	49	61	65	59	74	59	54	67	91%	●		
N45	NEF45SM3	4.5	4L/TC	M		M	81	75	93	73	67	84	87	80	100	79	72	91	92%	●		
N45 <sup>1</sup>	NEF45TM2A	4.5	4L/TAA	M		M	96	89	111	88	81	101	107	99	123	98	90	112	92%	●		
N45 <sup>1</sup>	NEF45TM3	4.5	4L/TAA	M		M	118	109	136	107	98	123	122	112	140	111	102	128	92%	○		
N67	NEF67SM1	6.7	6L/TC	M		M	121	111	139	110	101	127	138	127	159	126	115	144	92%	●		
N67 <sup>1</sup>	NEF67TM3A	6.7	6L/TAA	M		M	152	140	175	138	127	158	165	152	190	149	137	172	92%	●		
N67	NEF67TM4	6.7	6L/TAA	M		M	165	152	190	150	138	172	-	-	-	-	-	-	92%	○		
N67	NEF67TM7	6.7	6L/TAA	M		M	195	179	224	177	163	204	195	179	224	176	162	202	92%	●		
N67	NEF67TE8P	6.7	6L/TAA	ECR		ECR	239	219	274	216	199	248	254	233	292	230	211	264	92%	●		
CURSOR 9 <sup>1</sup>	CURSOR87TE4	8.7	6L/TAA	ECR		ECR	299	278	348	275	256	320	333	310	387	306	285	356	93%	●		
CURSOR 13 <sup>1</sup>	CURSOR13TE2A	12.9	6L/TAA	EUI		EUI	330	307	384	300	279	349	360	335	419	327	304	380	93%	●		
CURSOR 13 <sup>1</sup>	CURSOR13TE3A	12.9	6L/TAA	EUI		EUI	387	364	455	352	331	414	398	374	468	360	338	423	94%	●		
CURSOR 13	CURSOR13TE6W	12.9	6L/TAA	ECR		ECR	414	393	492	371	352	441	454	431	539	400	380	475	95%	●		
CURSOR 13	CURSOR13TE7W	12.9	6L/TAA	ECR		ECR	459	436	545	425	404	505	474	450	563	428	407	508	95%	●		
CURSOR 16 <sup>1</sup>	CURSOR16TE1W	15.9	6L/TAA	ECR		ECR	557	529	661	505	480	600	578	549	686	523	497	621	95%	●		

### Legend

**Cylinder Arrangement**  
L In line

**Exhaust System**  
I-EGR Internal Exhaust Gas Recirculation

**Injection System**  
M Mechanical  
ECR Electronic Common Rail  
EUI Electronic Unit Injector

● 1,500 / 1,800 rpm switchable engine  
○ Non-Switchable Engine

**Other Notes**  
kVA kiloVolt Ampere calculations based on a 0.8 power factor

**Air Intake**  
NA Naturally Aspirated  
TAA Turbocharged Aftercooler  
TC Turbocharged

**Emission Regulations**  
1 TUV measured based on TA-Luft standards